

CHERRY MX-Board 3.0



Models may vary from the image shown

Professional keyboard for fast and precise input

The CHERRY MX-Board 3.0 captivates with its world-exclusive use of Gold Crosspoint contacts in the MX modules, ensuring perfect and extremely fast keystrokes. This professional, maximum-precision keyboard is even sturdier and more robust than its predecessor, making it the perfect partner for every type of exacting input imaginable.

Key benefits

- Proved itself billions of times: Original CHERRY MX modules "made in Germany"
- World exclusive CHERRY Gold Crosspoint technology
- Four different keyswitches available: black, red, brown, blue
- 50 million+ operations for each key
- N-key rollover: Simultaneous operations of up to 14 keys without any key ghosting effects
- Win-Key lock: Windows buttons can be disabled
- The integrated metal plate and anti-slip protection ensure it remains robust
- Detachable cable

Technical Data:

Layout (country or language):

Product dependant, see table "Models"

Housing colour:

black

Key colour:

black

Weight (product):

approx. 830 g

Total weight (with packaging):

approx. 1215 g

Cable Length:

approx. 1.80 m

Storage Temperature:

-20°C to 60°C

Operating Temperature:

0°C to 50°C

Current Consumption:

max. 100 mA








Interface:

- USB

Connection sockets:

- 1 USB port (type mini B 5-pin)

Product approvals:

- cURus 
- c-tick 
- VCCI 
- CE 
- FCC 
- BSMI 
- KC 

System requirements:

- USB connection

Delivery Volume:

- CHERRY MX-Board 3.0
- Operating instructions in hard copy
- Detachable connection cable (USB A plug / USB mini B plug)
- 2 non-slip surfaces
- 2 rubber caps for adjustable feet

Dimensions (product):

approx. 446 x 158 x 28 mm

Packaging dimensions:

approx. 468 x 202 x 35 mm

Reliability:

- MTBF (90) > 80,000 hours

Keyboard:

- Key technology: MX
- Service life, standard key: > 50 million key operations
- Operation characteristics: Product dependant, see table "Models"
- Inscription technology: Laser
- Inscription layout: Standard
- Number of Keys: Product dependant, see table "Models"
- Number of additional keys: 4

Packaging Unit:

- Number of products in the master package: 8
- Number of master packages per pallet: 20

Warranty:

2 years

Errors, technical changes and delivery possibilities excepted. Technical information refers only to the specifications of the products. Features may differ from the information provided.

Models:


(possible country/layout versions, others available on request)

	Product name	Order number	EAN code	Layout (country or language)	Operation characteristics ¹	Number of Keys
1	CHERRY MX-Board 3.0	G80-3850LSAEU-2	4025112079696	US English with EURO symbol	BLUE SWITCH Click pressure point (60cN)	104+4
2	CHERRY MX-Board 3.0	G80-3850LSBEU-2	4025112080494	US English with EURO symbol	BLUE SWITCH Click pressure point (60cN)	104+4
3	CHERRY MX-Board 3.0	G80-3850LSBJA-2	4025112080586	Japan (Hiragana)	BLUE SWITCH Click pressure point (60cN)	109+4
4	CHERRY MX-Board 3.0	G80-3850LSBKO-2	4025112079702	Korea	BLUE SWITCH Click pressure point (60cN)	106+4
5	CHERRY MX-Board 3.0	G80-3850LSBKR-2	-	English (US) / Korean	BLUE SWITCH Click pressure point (60cN)	104+4
6	CHERRY MX-Board 3.0	G80-3850LSBTW-2	4025112080531	Taiwan	BLUE SWITCH Click pressure point (60cN)	104+4
7	CHERRY MX-Board 3.0	G80-3850LUAEU-2	4025112079641	US English with EURO symbol	BLACK SWITCH Linear (60 cN)	104+4
8	CHERRY MX-Board 3.0	G80-3850LUBEU-2	4025112080487	US English with EURO symbol	BLACK SWITCH Linear (60 cN)	104+4
9	CHERRY MX-Board 3.0	G80-3850LUBJA-2	4025112080579	Japan (Hiragana)	BLACK SWITCH Linear (60 cN)	109+4
10	CHERRY MX-Board 3.0	G80-3850LUBKO-2	4025112080555	Korea	BLACK SWITCH Linear (60 cN)	106+4
11	CHERRY MX-Board 3.0	G80-3850LUBKR-2	-	English (US) / Korean	BLACK SWITCH Linear (60 cN)	104+4
12	CHERRY MX-Board 3.0	G80-3850LUBTW-2	4025112080517	Taiwan	BLACK SWITCH Linear (60 cN)	104+4
13	CHERRY MX-Board 3.0	G80-3850LXAEU-2	4025112079818	US English with EURO symbol	BROWN SWITCH Pressure point (55cN)	104+4
14	CHERRY MX-Board 3.0	G80-3850LXBEU-2	4025112080500	US English with EURO symbol	BROWN SWITCH Pressure point (55cN)	104+4
15	CHERRY MX-Board 3.0	G80-3850LXBJA-2	4025112080593	Japan (Hiragana)	BROWN SWITCH Pressure point (55cN)	109+4
16	CHERRY MX-Board 3.0	G80-3850LXBKO-2	4025112080562	Korea	BROWN SWITCH Pressure point (55cN)	106+4


Product name	Order number	EAN code	Layout (country or language)	Operation characteristics ¹	Number of Keys	
17	CHERRY MX-Board 3.0	G80-3850LXBKR-2	-	English (US) / Korean	BROWN SWITCH Pressure point (55cN)	104+4
18	CHERRY MX-Board 3.0	G80-3850LXBTW-2	4025112080548	Taiwan	BROWN SWITCH Pressure point (55cN)	104+4
19	CHERRY MX-Board 3.0	G80-3850LYAEU-2	4025112079658	US English with EURO symbol	RED SWITCH Linear (45 cN)	104+4
20	CHERRY MX-Board 3.0	G80-3850LYBDE-2	4025112079764	Germany	RED SWITCH Linear (45 cN)	105+4
21	CHERRY MX-Board 3.0	G80-3850LYBEU-2	4025112080135	US English with EURO symbol	RED SWITCH Linear (45 cN)	104+4
22	CHERRY MX-Board 3.0	G80-3850LYBGB-2	4025112080944	UK	RED SWITCH Linear (45 cN)	105+4
23	CHERRY MX-Board 3.0	G80-3850LYBJA-2	4025112079733	Japan (Hiragana)	RED SWITCH Linear (45 cN)	109+4
24	CHERRY MX-Board 3.0	G80-3850LYBKO-2	4025112079719	Korea	RED SWITCH Linear (45 cN)	106+4
25	CHERRY MX-Board 3.0	G80-3850LYBKR-2	-	English (US) / Korean	RED SWITCH Linear (45 cN)	104+4
26	CHERRY MX-Board 3.0	G80-3850LYBTW-2	4025112080524	Taiwan	RED SWITCH Linear (45 cN)	104+4

1 Operation characteristics:


• BLACK SWITCH Linear (60 cN)



• BLUE SWITCH Click pressure point (60cN)



• RED SWITCH Linear (45 cN)



• BROWN SWITCH Pressure point (55cN)

