

공인네트워크관리사

<http://cafe.daum.net/icqanetworker> [

]

▶ 1

2

[1] Win98 PC TCP/IP Address					
, Ping Protocol Gateway					
[]					
IP Address: 210.111.129. x Host: ICQA					
Domain : netsgo.com Subnet Mask :255.255.255.0					
Dns Address: 210. 115 .125.37 Gateway : 210.111.129.254					
()		()			
1. PC TCP/IP Address 가	1. TCP/IP 가	Gateway			
	Ping		15		
2. 가 Win98	Test	가			
Mode	Display				
(Host: ICQA, Domain : netsgo.com, Subnet Mask :255.255.255.0,					
Dns Address: 210. 115 .125.37, Gateway : 210.111.129.254) setup IP address setup .					
setup gateway ping TCP/IP 가					
.					

10			
<p>3 3 class c 8 가</p> <p>3 , 2 가 .</p> <p>. 2</p> <p>0 0 0 0 0 0 0 0 . 3 2 가 .</p> <p>1 1 0 0 0 0 0 0 .</p> <p>10 128 + 64 = 192 가 . 255.255.255.192 가 .</p> <p>가 3 224 .</p> <p>0 256 .</p>			

<p>[3] Ping Protocol Gateway(210.111.129.254) IP</p> <p>Address</p> <p>()</p>			
<p>1. Ping IP datagram ,</p>			

<p>datagram</p> <p>2. , ?</p> <p>*</p> <p>PC TCP/IP</p>		5		
1		2		
<p>TTL .</p> <p>(Time To Live</p> <p>. Ping 가 .)</p>		<p>TTL = A(A numeric 32</p> <p>128 가 .)</p>		

<p>[4] Win NT "ICQA" Local Group , "ICQA" Local Group</p> <p>" "</p>				
()	()			

<p>1UTP 45</p> <p>RJ-</p>	<p>UTP RJ-45</p> <p>TEST</p> <p>[]</p> <p>가</p>	<p>RJ-45</p> <p>UTP Cable(1m)</p> <p>1</p> <p>Tool 1</p> <p>Test Tool 1</p>	<p>20</p>		
-------------------------------	--	---	-----------	--	--