

Date: _____ Driver: DARIO BALESTRI
 Event: WARM-UP WC LISBONA Car: G4 PLUS
 Track: LISBONA Weight: _____

SETUP SHEET



TRACK CONDITIONS			
Surface:	<input type="checkbox"/> Smooth	<input type="checkbox"/> Med.	<input type="checkbox"/> Bumpy
Size:	<input type="checkbox"/> Open	<input type="checkbox"/> Med.	<input type="checkbox"/> Tight
Traction:	<input type="checkbox"/> High	<input type="checkbox"/> Med.	<input type="checkbox"/> Low

Track Temp/Air Temp: _____° / _____°
 Note: _____

FRONT SUSPENSION

Front Width: 198 mm
 Anti-Roll Bar: 90°
 Diff. Fluid: 30'000 wt
 One Way
 Solid Axle
 Toe Angle: +1°
 Front Camber: L+2° R+2°
 Front Ride Height: 5 mm
 Front Droop: 2,5 mm
 Caster: 2 mm
 ▶ SHOCK
 Shock Length: 63 mm
 Thread Length: _____ mm
 Oil: 300 wt
 Piston: ORIGINAL
 Spring: BLU MUGEN mm
 ▶ TIRE
 Front Tire: ATS COSMIC
 Shore: L 37° R 37°
 Diameter(Start): L/R _____ mm
 Diameter(Finish): L/R _____ mm

REAR SUSPENSION

Rear Width: 200 mm
 Anti-Roll Bar: 0°
 Diff. Fluid: 20'000 wt
 Solid Axle
 Toe Angle: 2,5°
 Rear Camber: L 4° R 4°
 Rear Ride Height: 6 mm
 Rear Droop: 2 mm
 ▶ SHOCK
 Shock Length: 63 mm
 Thread Length: _____ mm
 Oil: 300 wt
 Piston: ORIGINAL
 Spring: GREEN TM mm
 ▶ TIRE
 Front Tire: ATS COSMIC
 Shore: L 37° R 37°
 Diameter(Start): L/R _____ mm
 Diameter(Finish): L/R _____ mm

PULLEY

Front Side Pulley: _____ T
 Rear Side Pulley: _____ T
 Brake Pulley: _____ T

ENGINE

Gear Ratio: 1st 16 T / 52 T
 2nd 21 T / 46 T
 Clutch Set Type:
 3 Shoe Push Type
 Clutch Spring: _____ mm
 Clutch weight: _____
 Clutch Shoe: _____
 Engine: NOVAROSI
 Plug: _____
 Fuel: DINNER TIME
 Manifold: _____
 Pipe: NOVA 2630
 Pipe Length: _____ mm

Note: _____

WHEELBASE

257 mm
 258 mm
 259 mm
 260 mm

BODY

Body: ALTI BLITZ
 Radio: SANWA
 ST. Servo: SANWA
 TH. Servo: SANWA